

TRAILHUNTER 850

TRIMS AVAILABLE: EPS, ULT, MUD

When you're ready to conquer rugged landscapes, reach remote areas, and amp up your outdoor adventures like exploration and hunting, the Trailhunter 850 is your perfect choice.

Main Features

Unrivaled Durability

You demand a vehicle that can take a beating, and SWM ORVs deliver. Every SWM Off-Road Vehicle is built on a high-yield strength alloy steel frame.

Engine with Superior Performance & Efficiency

Thanks to BOSCH EFI, our engine offers superior fuel efficiency, smoother power delivery, lower emissions, and an overall better driving experience. Its larger displacement, combined with EFI's precise control, optimizes performance for the next level.

Optimized Driving Comfort

Every SWM ORV features an innovative and highly reliable suspension system with 20% more travel than competitors in its class. This translates to superior off-road performance and enhanced driving comfort—you'll feel the difference.

Added Storage Capability

Our design features integrated front and rear sunken storage compartments, providing ample space for all your gear and adventure essentials.

Intelligent Options

Elevate your ride with our ATV's deluxe intelligent features, including: Tri-mode EPS, Engine Braking, Intelligent Throttle Control, multiple work modes (Eco/Std/Sport), Active Descent Control, Anti-theft, and Electric Gear Shift.





TRAILHUNTER 850 TRAILHUNTER TOURING 850



ENGINE TRANSMISSION	Displacement	850: 999cc, V-twin, DOHC, Liquid Cooled	
	Max Power / Torque	82HP / 90 N·m (66 lb-ft)	
CHASSIS HANDLING	Front Suspension	Double A-arm 10 in. (255 mm) travel	
	Rear Suspension	Double A-arm 10.43 in. (265 mm) travel	
	Shock Absorber	Oil shock absorber	
	Front Tires	27X9-14 in.	
	Rear Tires	27X11-14 in.	
	Rim	Aluminum alloy rim	
FEATURES	Gauge	7" TFT Display	
	Power Steering	EPS	
	Lighting	LED headlights and tail lights	
		TRAILHUNTER 850	TRAILHUNTER TOURING 850
DIMENSIONS CAPABILITIES	LxWxH	89.6×50.0×58.1 in. (2275x1270x1477 mm)	96.7×50.0×58.1 in. (2,455×1270×1477 mm)
	Wheel Base	52.5 in. (135 cm)	60.2 in. (153 cm)
	Ground Clearance	11.85 in. (30.1 cm)	11.85 in. (30.1 cm)
	Estimated Dry Weight*	924 lb (420 kg)	970 lb (440 kg)
	Towing Capacity	1,830 lb (830 kg)	1,830 lb (830 kg)



SWM MOTORCYCLES S.R.L. Via Nino Bixio, 8 21024 Biandronno (VA) – ITALY TEL.+39 0332 769911 FAX.+39 0332 769958

EMAIL: info@swm-motorcycles.it

American Headquaters:

American Shineray Co., Inc 875 Sandy Lake Rd Coppell, TX, 75019, US Mobile +945 745 7999 Email: gary.liao@shineray.com

Asia-Pacific Headquarters:

SWM Powersports Technology Co., Ltd No.1, No. 8, Xinyuan Road, Hangu Town, Gaoxin District Chongqing, 401329, China TEL. +86 023 65733319 EMAIL: info@swm-powersports.com











